

Bruder Kompressor S3 R 46

- Long Life
- Improved Efficiency

Premium Rotary Air Compressor Oil

Bruder Kompressor S3 R is a premium quality air compressor oil designed to deliver high performance lubrication of rotary sliding vane and screw air compressors. It uses an advanced additive system to provide excellent protection and performance for compressors running with oil maintenance intervals up to 4,000 hours (where allowed by manufacturers).

DESIGNED TO MEET CHALLENGES

Performance, Features & Benefits

- **Long oil life – Maintenance saving**

Bruder S3 R is capable of providing oil maintenance intervals of 4,000 hours (where allowed by manufacturers) even when operating at maximum discharge temperatures of up to 100°C.

It is formulated to help:

- Resist formation of carbon deposits in sliding vane slots in vane compressors
- Resist formation of deposits on rotating components in screw compressors
- Resist thermal breakdown and deposit formation to maintain excellent internal surface cleanliness particularly in oil/air separator and coalescer systems.
- The exact oil maintenance interval will depend on intake air quality, duty cycle and ambient conditions. For hot and humid type climates as found in the Asian and Pacific regions, oil drain period below 4,000hrs is recommended (also consult OEM recommendations).
- **Outstanding wear protection**
With many years of successful application, Bruder S3 R helps provide effective protection of internal metal surfaces from corrosion and wear.

It contains an advanced ashless anti-wear system to help prolong the life of critical parts such as bearings and gears.

- **Maintaining system efficiency**

Air release and prevention of foaming are critical performance characteristics in a compressor oil, ensuring reliable start-up and continuous compressed air availability. Bruder S3 R is designed to provide rapid air release without excessive foaming to give trouble-free operation even under cycling conditions.

In addition, Bruder S3 R has excellent water separation properties to help ensure continuous efficient operation of the compressor even in the presence of water.

Main Applications



- **Rotary sliding vane and screw air compressors**

Bruder S3 R is suitable for use in oil-flooded/ oil injected single or two-stage rotary vane or screw air compressors.

Specifications, Approvals & Recommendations

- ISO 6743-3:2003(E) L-DAJ

For a full listing of equipment approvals and recommendations, please consult your dealer or agent.

Compatibility & Miscibility

- **Seal Compatibility**

Bruder S3 R oils are compatible with seal materials specified for use with mineral oils.

Typical physical Characteristics

Properties			Method	Bruder S3 R 46
ISO Viscosity Grade			ISO 3448	46
Kinematic Viscosity	@40°C	mm ² /s	ASTM D445	46
Kinematic Viscosity	@100°C	mm ² /s	ASTM D445	6.9
Viscosity Index			ISO 2909	105
Density	@15°C	kg/m ³	ASTM D 1298	868
Flash Point (COC)		°C	ASTM D 92	230
Air Release		mins	ASTM D 3427	3
Rotating Pressure Vessel Oxidation Test (RPVOT)		mins	ASTM D 2272	700
FZG Test		LS Fail	CEC-L-07-A-95	11
Pour Point		°C	ASTM D 97	-30
Water Separability	@54°C	mins	ASTM D 1401	15

These characteristics are typical of current production. Whilst future production will conform to manufacturer's specification, variations in these characteristics may occur.

Health, Safety & Environment

• Health and Safety

Bruder S3 R is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <http://www.bruderaustralia.com.au/bruderkompressorextras/service-kit>

• Protect the Environment


Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

• Advice

Advice on applications not covered here may be obtained from your sales representative.

Viscosity - temperature diagram for Bruder S3 R 46



Technical Helpdesk 1800 088 990

Bruder Australia Pty Ltd
(ABN 95 627 272 573)
32 Secker Road
Wint Barker SA 5251